



SCHRAUBERZUBEHÖR


Schraubendrehereinsätze





Klingenaufnahme: Sechskant 1/4", DIN 3126, Form E/F

für Schlitz-Schrauben	Artikel-Nr.	Ø mm	L mm
	291 00 032	3,0	50
	291 00 033	3,0	70
	291 00 034	3,5	50
	291 00 035	3,5	70
	291 00 036	4,0	50
	291 00 037	4,0	70
	291 00 039	5,0	50
	291 00 040	5,0	70
	291 00 042	5,5	50
	291 00 043	5,5	70
	291 00 045	6,0	50
	291 00 046	6,0	70
	291 00 048	7,0	50
	291 00 049	7,0	70
	291 00 051	8,0	50
	291 00 052	8,0	70

für Innensechskant-Schrauben	Artikel-Nr.	SW	L mm
	291 00 313	2,5	50
	291 00 315	3	50
	291 00 316	3	70
	291 00 319	4	50
	291 00 320	4	70
	291 00 323	5	50
	291 00 324	5	70
	291 00 327	6	50
	291 00 328	6	70
	291 00 331	8	50
	291 00 332	8	70

für Außensechskant-Schrauben	Artikel-Nr.	SW	L mm
	291 00 426	5	50
	291 00 432	5,5	50
	291 00 438	6	50
	291 00 444	7	50
	291 00 450	8	50
	291 00 456	9	50
	291 00 462	10	50
	291 00 468	11	50
	291 00 472	12	50
	291 00 476	13	50
	291 00 480	14	50


für Phillips-Schrauben	Artikel-Nr.	Größe	L mm
	291 00 251	PH 1	50
	291 00 252	PH 1	70
	291 00 254	PH 1	152
	291 00 259	PH 2	50
	291 00 260	PH 2	70
	291 00 262	PH 2	152
	291 00 267	PH 3	50
	291 00 268	PH 3	70
	291 00 270	PH 3	152

für Pozidriv-Schrauben	Artikel-Nr.	Größe	L mm
	291 00 255	PD 1	50
	291 00 256	PD 1	70
	291 00 258	PD 1	152
	291 00 263	PD 2	50
	291 00 264	PD 2	70
	291 00 266	PD 2	152
	291 00 271	PD 3	50
	291 00 272	PD 3	70
	291 00 274	PD 3	152

Verbinder für Steckschlüssel



Klingenaufnahme: Sechskant 1/4"

	Artikel-Nr.	Aufnahme	L mm
	291 00 591	Vierkant 1/4"	51
	291 00 592	Vierkant 1/4"	102
	291 00 593	Vierkant 3/8"	51
	291 00 594	Vierkant 3/8"	102
	291 00 588	Vierkant 1/2"	51
	291 00 598	Vierkant 1/2"	102

Bithalter



Klingenaufnahme: Sechskant 1/4"

	Artikel-Nr.	L mm
	291 20 015	51
	291 20 014	75
	291 20 020	74 SWF

SWF - Schnellwechselfutter

Bits

Bitaufnahme: 1/4", DIN 3126, Form C/D



Pozidriv-Bits	Artikel-Nr.	Größe	L mm
	291 20 131	PH 0	25
	291 20 132	PH 1	25
	291 20 136	PH 2	25
	291 20 140	PH 3	25

Innensechskant-Bits	Artikel-Nr.	SW mm	L mm
	291 20 152	1,5	25
	291 20 153	2	25
	291 20 154	2,5	25
	291 20 155	3	25
	291 20 157	4	33
	291 20 159	5	33
	291 20 161	6	33
	291 20 162	8	33
291 20 163	10	33	


Torx-Bits	Artikel-Nr.	Ø	L mm
	291 20 112	T 05	25
	291 20 113	T 06	25
	291 20 114	T 07	25
	291 20 115	T 08	25
	291 20 116	T 09	25
	291 20 117	T 10	25
	291 20 118	T 15	25
	291 20 119	T 20	25
	291 20 120	T 25	25
	291 20 121	T 27	25
	291 20 122	T 30	25
	291 20 123	T 40	25

Pozidriv-Bits	Artikel-Nr.	Größe	L mm
	291 20 134	PH 1	25
	291 20 138	PH 2	25
	291 20 142	PH 3	25

Schlitz-Bits	Artikel-Nr.	Ø mm	L mm
	291 20 180	3,2	25
	291 20 188	3,6	25
	291 20 181	3,9	25
	291 20 182	4,7	25
	291 20 190	5,5	25
	291 20 194	6,3	25

Steckschlüssel

für Außensechskant,
Aufnahme Vierkant 1/4" – 1 1/2",
DIN 3126



Aufnahme: 1/4"	Artikel-Nr.	SW mm	L mm	D1 mm	D2 mm
Artikel-Nr. Ring und Stift 292 00 201	291 20 112	4	25	7,7	13
	291 20 113	5	25	8,9	13
	291 20 114	5,5	25	9,5	13
	291 20 115	6	25	10,2	13
	291 20 116	7	25	11,4	13
	291 20 117	8	25	12,7	13
	291 20 118	10	25	15,3	13
	291 20 119	13	25	19,1	13

Aufnahme: 3/8"	Artikel-Nr.	SW mm	L mm	D1 mm	D2 mm
Artikel-Nr. Ring und Stift 292 50 201	292 50 151	7	34	12,5	19
	292 50 152	5	34	13,8	19
	292 50 154	5,5	34	16,4	19
Artikel-Nr. Ring und Stift 292 00 202	292 50 157	13	34	20,2	22
	292 50 158	14	34	21,5	22
	292 50 161	17	34	25,4	22
	292 50 161	19	34	27,9	22


Aufnahme: 1/2"	Artikel-Nr.	SW mm	L mm	D1 mm	D2 mm
Artikel-Nr. Ring und Stift 293 00 201	293 00 153	10	40	17,6	25
	293 00 156	13	40	21,4	25
	293 00 157	14	40	22,7	25
Artikel-Nr. Ring und Stift 293 00 202	293 00 160	17	40	26,6	30
	293 00 162	19	40	29,1	30
	293 00 165	22	40	32,9	30
	293 00 167	24	45	35,4	30
	293 00 170	27	50	39,3	30
	293 00 172	30	50	43	30

Aufnahme: 3/4"	Artikel-Nr.	SW mm	L mm	D1 mm	D2 mm
Artikel-Nr. Ring und Stift 293 50 201	293 50 155	17	50	30	44
	293 50 157	19	50	32,5	44
	293 50 160	22	50	36,5	44
	293 50 162	24	50	38,9	44
	293 50 165	27	50	42,5	44
	293 50 168	30	53	46,5	44
	293 50 170	32	53	48,8	44
	293 50 174	36	55	53,8	44
	293 50 176	41	57	60	44
	293 50 177	46	62	66,5	44

Aufnahme: 1"	Artikel-Nr.	SW mm	L mm	D1 mm	D2 mm
Artikel-Nr. Ring und Stift 294 00 201	294 00 135	32	62	51,5	54
	294 00 136	36	62	56,6	54
	294 00 138	41	66	62,8	54
	294 00 139	46	70	69	54
	294 00 140	50	70	74	54
	294 00 141	55	75	80,5	54
	294 00 142	60	75	86,5	54

Aufnahme: 1 1/2"	Artikel-Nr.	SW mm	L mm	D1 mm	D2 mm
Artikel-Nr. Ring und Stift 294 50 201	294 00 130	55	90	85	86
	294 00 131	60	90	91	86
	294 00 132	65	95	97	86
	294 00 133	70	100	103	86
	294 00 134	75	105	108	86
	294 00 135	80	110	115	86
	294 00 136	85	110	122	86
	294 00 137	90	112	128	86
	294 00 138	95	112	135	86
	294 00 139	100	115	140	86
	294 00 141	110	124	153	86
	294 00 142	115	128	160	86

Antrieb für Innensechskant-Schrauben



Aufnahme: Vierkant 3/8"	Artikel-Nr. Einsatz	SW
Artikel-Nr. 293 00 118	291 20 102	5
	291 20 103	6
	291 20 104	8
	291 20 105	10
	291 20 106	12
	291 20 107	14

Aufnahme: Vierkant 1/2"	Artikel-Nr. Einsatz	SW
Artikel-Nr. 293 00 118	291 20 112	5
	291 20 113	6
	291 20 114	8
	291 20 115	10
	291 20 116	12
	291 20 117	14

Adapter



Artikel-Nr.	Innen	Außen
292 00 145	□ 1/4"	□ 3/8"
292 50 196	□ 3/8"	□ 1/4"
292 50 198	□ 3/8"	□ 1/2"
293 00 188	□ 1/2"	□ 3/8"
293 00 197	□ 1/2"	□ 3/4"
293 50 141	□ 3/4"	□ 1/2"
293 50 143	□ 3/4"	□ 1"
294 50 171	□ 1"	□ 3/4"
294 50 171	□ 1 1/2"	□ 1"

Verlängerungen



Artikel-Nr.	Aufnahme	Länge mm
292 00 140	□ 1/4"	150
292 50 187	□ 3/8"	150
293 00 184	□ 1/2"	175
293 50 188	□ 3/4"	175
294 00 184	□ 1"	175

Bit-Halter



Artikel-Nr.	Vierkant	Länge mm
292 00 110	1/4"	26
292 50 110	3/8"	31
293 00 110	1/2"	38

Schnellwechselfutter



Artikel-Nr.	Innenvierkant	Innensechskant	Länge mm
292 00 143	1/4"	1/4"	38
292 50 143	3/8"	1/4"	45

Haltefeder für Steckschlüssel



Artikel	Artikel-Nr.	Antrieb	Innen-Ø mm
HF 19	292 50 180	3/8" Vierkant	17,2
HF 22	292 50 181	3/8" Vierkant	19,6
HF 25	293 00 180	1/2" Vierkant	22,5
HF 30	293 00 181	1/2" Vierkant	27,6
HF 44	293 50 180	3/4" Vierkant	40,5
HF 54	294 00 180	1" Vierkant	49,5

Halbmondklingen 4 mm



Für Kreuzschlitz-Schrauben	Artikel-Nr.	Ø x Arbeitslänge / Gesamtlänge in mm
✕	Größe 00	379 99 701 2 x 20 / 44
		379 99 711 2 x 20 / 64
Größe 0		379 99 702 1,8 x 20 / 44
		379 99 703 2 x 20 / 44
		379 99 704 2,5 x 20 / 44
		379 99 705 3 x 20 / 44
Größe 1		379 99 706 4 / 44
	Größe 2	379 99 707 4 / 44

Für Schlitz-Schrauben	Artikel-Nr.	Arbeitslänge / Gesamtlänge in mm
	2 mm	379 99 721 20 / 44
	2,5 mm	379 99 722 20 / 44
	3 mm	379 99 723 20 / 44
	4 mm	379 99 724 20 / 44
	5 mm	379 99 725 20 / 44

für Innensechskant-Schrauben	Artikel-Nr.	Gesamtlänge in mm
⬡	SW 1,5	379 99 731 44
	SW 2	379 99 732 44
	SW 2,5	379 99 733 44
	SW 3	379 99 734 44
	SW 4	379 99 735 44

Für Torx-Schrauben	Artikel-Nr.	Gesamtlänge in mm
⬠	T2	379 99 742 44
	T3	379 99 743 44
	T4	379 99 744 44
	T5	379 99 745 44
	T8	379 99 748 44

für Außensechskant-Schrauben	Artikel-Nr.	Gesamtlänge in mm
⬢	SW 2,3	379 99 761 44
	SW 2,5	379 99 762 44
	SW 3	379 99 763 44
	SW 4	379 99 764 44
	SW 4,5	379 99 765 44
	SW 5	379 99 766 44
	SW 5,5	379 99 767 44