

# Battery-Operated Hydraulic Crimping / Cutting / Bending Tool

# TRILINER C

#### **Technical Data**

Crimping / Cutting Force	70 kN
Opening Width	30 mm (Cu/Al) 20 mm (Al/St)
Battery Voltage	18 V
Weight*	2.1 kg
Dimensions* L x W x H	375 x 75 x 95 mm
Stroke	21 mm

<sup>\*</sup> without battery and attachment

MasterBase technology offers the following battery options, select your tool here:

Item No.	Item	Suitable for batteries from
78002100	TriLiner C Ma	Makita 18 V
78102100	TriLiner C-Set Ma**	Makita 18 V
76002600	TriLiner C Bo	Bosch 18 V
78002900	TriLiner C Hi	Hilti 22 V (B22)
78002600	TriLiner C Mi	Milwaukee 18 V

Crimping, cutting and bending: This tool cuts Cu cable and

shaped crimping dies (CS) up to 240 mm<sup>2</sup> to DIN or bends cable up to 1,000 mm<sup>2</sup>. The pull-pin head ensures quick and easy installation. The tool is therefore ideal for electrical installation with changing areas of application - with a

ACSR; crimps cable lugs or connectors with narrow C-

bending attachment especially for installation work in

shafts or electrical installations in angled areas.



\*\*Scope of Delivery Set: TriLiner C Ma, Makita battery The tool attachments are not included.

### **Top Features Comfort Serie "TriLiner C"**

- » Equipped with MasterBase technology for flexible selection of the Makita or Bosch battery
- » Interchangeable head allows three applications
- » Design ideally for working in narrow areas
- » Automatic return simplifies the work process
- » Fatigue-free working through ergonomic, lightweight construction
- » LED working field illumination
- » Improved Bending tool SLCB-JAW-1 for

18 V/5 Ah BL1850B (Item No. 793000115), Makita battery charger DC18RC (Item No. 79300120), transportation case

#### **Attachments**

Crimping Head SL-6CJ

Crimping Die Series CS (narrow C-shaped)

Item No. 78002010

**Cutting Head Cable SL-CH** Item No. 78002020

**Cutting Head Cable SL-ASCR** 

Item No. 78002030

Cable Bender SLCB-JAW-1

Item No. 78002041



### **Crimping Head**

SL-6CJ		Cable	
Cu/Al to DIN 48083	$\bigcirc$	Cu: 6 - 240 mm <sup>2</sup> Al: 10 - 240 mm <sup>2</sup>	
ACSR	$\bigcirc$	Al: 16 – 185 mm <sup>2</sup> St: 2.5 – 25 mm <sup>2</sup>	
Tubular Cable Connector (similar to DIN)	$\bigcirc$	10 – 240 mm <sup>2</sup>	



A sample processing is recommended. Inquiry to P +49 40 511 28-0.

## Cutting Head Cu/Al

SL-CH		
Opening Width	Max. Ø 30 mm	
Application	Cu/Al Strand Cu/Al Energy Cable	
Item No.	78002020	



## **Cutting Head ACSR**

SL-ACSR	
Opening Width	Max. Ø 20 mm
Application	ACSR single steel core
Item No.	78002030



### Cable Bender

SLCB-JAW-1	
Cable max.	Ø 1,000 mm² (Ø 30 mm)
Item No.	78002041



### Accessories

Item	Туре	Description	Item No.	
Transportation Case	KOFF-Km Tri C	Light-weight plastic case with a compartment for two batteries, battery charger	79500138	COMMUNICATION CONTRACTOR CONTRACT
Carrying Strap	TR-REC	Carrying strap for battery tools, strap 25 mm wide, 1 snap hook	07542106	
	TR-25-2	Carrying strap for battery tools, strap 25 mm wide, 2 snap hooks	07755001	
	TR-40-2	Carrying strap for battery tools, strap 40 mm wide, 2 snap hooks	07755002	

Do you have a Comfort Series tool with an unsuitable battery holder? Talk to us, with Retrofit we can make it fit your requirements.