

AP 550-05-850

BATTERY-OPERATED HYDRAULIC PUMP

The **AP550-05-850 battery-powered hydraulic pump** is a mobile, powerful and flexible hydraulic unit for heavy-duty applications up to 850 bar. It has been specially developed for professional use in the energy industry, municipal utilities, the electrical and cable industry, and for service and infrastructure applications. With its position-independent use, robust aluminium housing and compatibility with common 18 V batteries, it offers maximum flexibility and efficiency – even under difficult construction site conditions.



Fits all OEM
batteries

- **Maximum flexibility**

Thanks to MasterBase technology, compatible with 18 V Makita, Bosch, Milwaukee and 22 V Hilti (B22) – integration into existing battery fleets saves costs and increases versatility.

- **High mobility**

Weighs only 10 kg including oil – easy to transport and flexible use at any work site, even without mains power.

- **Efficient working**

0.55 l/min delivery volume at up to 850 bar ensures fast results with crimping, cutting or punching tools.

- **Safe and maintenance-friendly design**

Indicator light signals upcoming maintenance, oil refilling possible via easily accessible oil tank screw, robust construction for long service life.

- **Versatile applications**

Position-independent use, hand-held remote control for precise control, CEJN Series 115 coupling for common hydraulic connections.

With the AP550-05-850 battery-powered hydraulic pump, you can work quickly and safely anywhere. It delivers high performance for powerful applications, can be integrated into any standard battery platform and impresses with its extremely robust, maintenance-friendly design.

Scope of Delivery:

Pump with remote control 3 m

Battery, charger and hose have to be ordered separately.

Optional:

Pressure can be set from 100 – 850 by the manufacturer

TECHNICAL DATA

Item	AP 550-05-850
Oil Delivery	0,55 l/min
Oil Fill	0,5 l (0,45 l useable)
Voltage	2 x 18 V DC
Weight*	10 kg
Dimensions	375 x 150 x 215 mm
Working Pressure	850 bar

* without battery

MasterBase technology offers the following battery options, select your tool here:

Item No.	Item	Suitable for batteries from
74338500	AP550-05-850 Ma	Makita 18 V Li-Ion
On request	AP550-05-850 Bo	Bosch 18 V Li-Ion
On request	AP550-05-850 Mi	Milwaukee 18 V Li-Ion

ZUBEHÖR

Item	Type	Description	Item No.	
Li-Ion-Battery Makita 18 V	BL1850B	Capacity: 5.0 Ah Weight: 0.64 kg Charger: DC18RC Charging Time: 45 min ($\pm$ 100 %)	79300115	
Double Quick Battery Charger	DC18RD	Voltage: 220 – 240 V Frequency: 50 – 60 Hz Output Voltage: 2 x 18 V Weight: 2,1 kg Dimensions: 205x340x100mm	79300121	
Quick Battery Charger	DC18RC	Voltage: 220 – 240 V Frequency: 50 – 60 Hz Output Voltage: 18 V Weight: 0.9 kg Dimensions: 156x190x84 mm	79300120	
Databox	AP550-Datenbox	USB interface; Readout of: Crimping / cutting cycles, operating hours of the motor, voltage of the batteries, time-pressure diagrams of the last 100 cycles as well as maximum pressure with time / date stamp, exportable in PDF format, maintenance intervals, due date of the next maintenance.	74339910	

Item	Description	Item No.
Hydraulic Hose, Oil Filling and Coupling included	2 m, max. 1.000 bar	79500010
	3 m, max. 1.000 bar	79500011
	6 m, max. 1.000 bar	79500012
	10 m, max. 1.000 bar	79500013