

Battery-operated Mechanical Cutting Tool

RS-C7

Technical Data

Opening Width	65 mm
Battery Voltage	18 V
Weight*	2.8 kg
Dimensions* L x W x H	117 x 232 x 356 mm

* without battery

MasterBase technology offers the following battery options, select your tool here:

Item No.	Item	Suitable for batteries from
72027000	RS-C7 Ma	Makita 18 V
72127000	RS-C7-Set Ma**	Makita 18 V
72068500	RS-C7 Bo	Bosch 18 V
72168500	RS-C7-Set Bo**	Bosch 18 V
72067000	RS-C7 Hi	Hilti 22 V (B22)
72070800	RS-C7 HiN	Hilti 22 V (Nuron)*
72069400	RS-C7 Mi	Milwaukee 18 V

* Time required to connect the battery to the tool: 2 s







The cable cutter precisely and quickly cuts non-armoured Al-cable of up to NAYY 4 x 240 mm² as well as Cu cable up to NYY 4 x 185mm² with cutting Ø up to 65 mm. In power supply and cable processing, this lightweight and ergonomic tool convinces with its sickle-shaped cutting geometry.

Top Features Comfort Serie "RS-C7"

- » Equipped with MasterBase technology for flexible selection of the Makita, Bosch or Hilti battery
- » Selectable automatic return for efficient work
- » Comfort through freely definable opening width adjustment
- » Clean cutting pattern
- » LED working field illumination
- » Does the Comfort Series tool not have the right battery holder? Retrofit will make it fit.



Cutting Ranges

Application	Cutting Ø	
Cu Strand	Ø 65 mm	
Al Strand	Ø 65 mm	
Cu Energy Cable	Ø 65 mm NYY 4 x 185 mm ² , 1 x 800 mm ²	
Al Energy Cable	Ø 65 mm NAYY 4 x 240 mm ² , 1 x 1.000 mm ²	

A sample processing is recommended.

**Scope of Delivery Sets:

72127000: RS-C7 Ma, Makita battery 18 V/5 Ah BL1850B (item no. 79300115), Makita charger DC18RC (item no. 79300120), transportation case (item no. 79500129)

72168500: RS-C7 Bo, Bosch battery PRO GBA 18V 5.0Ah (item no. 79300122), Bosch charger PRO GAL 1880CV (item no. 79300123), transportation case (item no. 79500129)