

Battery-Operated Hydraulic Crimping / Cutting / Bending Tool

TRILINER C

Technical Data

Crimping / Cutting Force	70 kN
Opening Width	30 mm (Cu/Al) 20 mm (Al/St)
Battery Voltage	18 V
Weight*	2.1 kg
Dimensions* L x W x H	375 x 75 x 95 mm
Stroke	21 mm

* without battery and attachment

MasterBase technology offers the following battery options, select your tool here:

Item No.	Item	Suitable for batteries from
78002100	TriLiner C Ma	Makita 18 V
78102100	TriLiner C-Set Ma**	Makita 18 V
76002600	TriLiner C Bo	Bosch 18 V
78003500	TriLiner C-Set Bo**	Bosch 18 V
78002900	TriLiner C Hi	Hilti 22 V (B22)
78003300	TriLiner C HiN	Hilti 22 V (Nuron)*
78002600	TriLiner C Mi	Milwaukee 18 V

* Time required to connect the battery to the tool: 2 s



Crimping, cutting and bending: This tool cuts Cu cable and ACSR; crimps cable lugs or connectors with narrow C-shaped crimping dies (CS) up to 240 mm² to DIN or bends cable up to 1,000 mm². The pull-pin head ensures quick and easy installation. The tool is therefore ideal for electrical installation with changing areas of application - with a bending attachment especially for installation work in shafts or electrical installations in angled areas.

Top Features Comfort Serie "TriLiner C"

- » Equipped with MasterBase technology for flexible selection of the Makita or Bosch battery
- » Interchangeable head allows three applications
- » Design ideally for working in narrow areas
- » Automatic return simplifies the work process
- » Fatigue-free working through ergonomic, lightweight construction
- » LED working field illumination
- » Improved Bending tool SLCB-JAW-1 for
- » Does the Comfort Series tool not have the right battery holder? **Retrofit** will make it fit.

**Scope of Delivery Sets:

78102100: TriLiner C Ma, Makita battery 18 V/5 Ah BL1850B (Item No. 79300115), Makita battery charger DC18RC (Item No. 79300120), transportation case (item no. 79500138)

78003500: TriLiner C Bo, Bosch battery PRO GBA 18V 5.0Ah (item no. 79300122), Bosch charger PRO GAL 1880CV (item no. 79300123), transportation case (item no. 79500138)

The tool attachments are not included.

Attachments




Crimping Head SL-6CJ
Crimping Die Series CS (narrow C-shaped)
Item No. 78002010

Cutting Head Cable SL-CH
Item No. 78002020

Cutting Head Cable SL-ACSR
Item No. 78002030

Cable Bender SLCB-JAW-1
Item No. 78002041

Crimping Head

SL-6CJ		Cable
Cu/Al to DIN 48083		Cu: 6 – 240 mm ² Al: 10 – 240 mm ²
ACSR		Al: 16 – 185 mm ² St: 2.5 – 25 mm ²
Tubular Cable Connector (similar to DIN)		10 – 240 mm ²
Item No.		78002010



A sample processing is recommended. Inquiry to P +49 40 511 28-0.

Cutting Head Cu/Al

SL-CH	
Opening Width	Max. Ø 30 mm
Application	Cu/Al Strand Cu/Al Energy Cable
Item No.	78002020



Cutting Head ACSR

SL-ACSR	
Opening Width	Max. Ø 20 mm
Application	ACSR single steel core
Item No.	78002030



Cable Bender

SLCB-JAW-1	
Cable max.	Ø 1,000 mm ² (Ø 30 mm)
Item No.	78002041

