



FORCE

80 kN

PERFORMANCE WITH 5.0 AH BATTERY

approx. 100 cycles

FEATURES

- Guillotine closed cutting head with bolt lock for secure operation.
- Reliable cutting of cables, overhead conductors, and solid materials.
- Ergonomic design optimised for overhead work.

APPLICATION

Cutting of power and underground cables, overhead utility lines as well as round material.

SPECIFICATIONS

Material / Conductor size and Diameter	Aluminum		
	Cutting (class 1, 2)	max. Ø 57 mm	up to 4x240 mm ² se (0.6/1 kV)
	ACSR	max. Ø 44.5 mm	up to 1,120 mm ²
	Aldrey (AL3)	max. Ø 46.7 mm	up to 1,120 mm ²
	Round material	max. Ø 28 mm	
	Copper		
	Cutting (class 1, 2)	max. Ø 54 mm	up to 4x185/95 mm ² sm (6/10 kV)
	Round material	max. Ø 35 mm	
	Steel		
	Wire rope	max. Ø 30 mm	6 x 7 / 6 x 12 / 6 x 19
	Reinforcing Rod	max. Ø 20 mm	
Force	80 kN		
Opening Width	55 mm		
Battery Voltage	18 V (compatible with Makita)		
Weight	8.65 kg		
Dimensions* L x B x H	537 x 80 x 388 mm		
Cutting Head	Guillotine closed, 360° rotatable		
Shape	pistol grip		

* Supplied in a lightweight plastic case (battery and charger not included).

SHOP ONLINE NOW: [SELECTED-TOOLS.DE](https://selected-tools.de)

INDUSTRIES

Energy suppliers, grid operators, overhead utility line construction, electrical engineering, solar technology

ACCESSORIES

Item	Type	Description	Part no.
Li-ion Battery Makita 18 V*	BL1850B	Capacity: 5.0 Ah Weight: 0.64 kg Charger: DC18RC Charging time: 45 min (100 %)	79300115
Quick charger	DC18RC	Voltage: 220 – 240 V Frequency: 50 – 60 Hz Output voltage: 18 V Weight: 0.9 kg Dimension (mm): 156 x 190 x 84	79300120
Battery adapter BO	HC-ADAP-BO-18V	Adapter compatible with Bosch (18V)	79300092
Battery adapter MI	HC-ADAP-MI-18V	Adapter compatible with Milwaukee (18V)	79300093
Battery adapter DE	HC-ADAP-DE-18V	Adapter compatible with Dewalt (18V)	79300094