


 Schneidbereiche / Cutting Ranges HOLGER CLASEN GmbH & Co. KG Alsterdorfer Straße 228 22297 Hamburg holger-clasen.de																						
Werkzeug	Schneidkraft [kN]	max. Schneid- Ø [mm]	Kopf	Seil Cu [mm]	Seil Al [mm]	Energiekabel Cu [mm]	Energiekabel Al [mm]	Fein/feinstdrähige Leiter Cu [mm]	Fein/feinstdrähige Leiter Al [mm]	Rundmaterial Cu [mm]	Rundmaterial Al [mm]	Al-St-Seil [mm]	St Anteil [mm²]	Telefonkabel [mm]	Bleiummanteltes Telefonkabel [mm]	Rundstahl [mm]	Drahtseil [mm]			Abspanndraht [mm]		Bewehrungsstahl [mm]
Tool	Cutting Force [kN]	max. Cutting Ø [mm]	Head	Strand Cu [mm]	Strand Al [mm]	Energy Cable Cu [mm]	Energy Cable Al [mm]	fine stranded conductors Cu [mm]	fine stranded conductors Al [mm]	round Cu [mm]	round Al [mm]	ACSR [mm]	St part [mm²]	Telephone cable [mm]	Lead Sheated Cable (Telephone cable) [mm]	round steel [mm]	wire rope			Guy wire		Reinforcing rod [mm]
																	6x7	6x12	6x19	1x17	1x19	
RS-C3-O	-	33	offen	33	33	33	33	-	-	24	30	18,6	35	-	-	-	-	-	-	-	-	-
RS-C5	-	50	geschlossen	50	50	50	50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
RS-C5-F	-	50	geschlossen	-	-	-	-	50	50	-	-	-	-	-	-	-	-	-	-	-	-	-
RS-C5-O	-	50	offen	50	50	50	50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
RS-C6	-	54	geschlossen	-	-	-	-	-	-	-	-	54	70	-	-	-	-	-	-	-	-	-
RS-C7	-	65	geschlossen	65	65	65	65	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
RS-C7-F	-	65	geschlossen	-	-	-	-	65	65	-	-	-	-	-	-	-	-	-	-	-	-	-
InLiner®-CS2	85	24	geschlossen	24	24	24	24	-	-	18	24	24	53	-	-	20	18	24	24	20	20	16
InLiner®-CS3	60	30	offen	28	28	28	28	optional	optional	-	-	-	-	20	-	-	18	24	24	20	20	
DuoLiner-C	58	30	offen	30	30	30	30	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
TriLiner-C	70	30 / 20	offen	30	30	30	30	-	-	-	-	20	Einzel- ader	-	-	-	-	-	-	-	-	-
CutMax-C2	84	24	geschlossen	24	24	24	24	-	-	18	24	24	53	-	-	20	18	24	24	20	20	16
CutMax-C3	60	30	offen	28	28	28	28	-	-	-	-	-	-	20	-	-	18	24	24	20	20	-
CutMax-C4	70	42	geschlossen	42	42	42	42	-	-	20	22	38	79	-	-	20	22	22	22	15	20	-
CutMax-C45	70	45	geschlossen	45	45	45	45	-	-	20	22	45	79	-	-	20	22	25	25	20	20	16
CutMax-C11	124	105	offen	105	105	105	105	-	-	-	-	-	-	105	-	-	-	-	-	-	-	-
InLineBox-CS6	120	54	geschlossen	54	54	54	54	-	-	35	28	54	-	-	-	22	25	30	30	15	20	19
InLineBox-CS11	124	105	offen	105	105	105	105	-	-	-	-	-	-	105	-	-	-	-	-	-	-	-
InLineBox-CS13	134	132	geschlossen	-	-	132	132	-	-					132	132						-	-
SH 20-B	39	22	geschlossen	22	22	22	22	-	-	18	22	22	56	-	-	16	16	20	20	21	21	13
SH 20-E	39	23	geschlossen	23	23	23	23	-	-	18	23	23	56	-	-	16	16	20	20	21	21	13
SH 24-A	76	24	geschlossen	24	24	24	24	-	-	18	24	24	53	-	-	20	18	24	24	20	20	16
SH 32-B	196	32	geschlossen	32	32	32	32	-	-	32	32	32	79	-	-	25	32	32	32	32	32	25
SH 45-A	55	45	geschlossen	45	45	45	45	-	-	22	20	45	79,38	-	-	20	22	25	25	20	20	16
SH 50-A	50	50	geschlossen	50	50	50	50	-	-	-	-	-	-	50	-	-	-	-	-	-	-	-
SH 55-B	120	54	geschlossen	54	54	54	54	-	-	28	32	50	85	-	-	22	25	30	30	15	20	19
SH 85-CR	70	85	geschlossen	28	38	85	85	-	-	-	28	-	-	85	-	-	-	-	-	-	-	-
PH 30	66	30	offen	28	28	28	28	-	-	-	-	19	46	30	30	-	-	-	-	-	-	-
PH 32-GA	250	32	geschlossen	32	32	32	32	-	-	32	32	32	79	-	-	25	32	32	32	32	32	-
PH 40-AG	77	42	geschlossen	42	42	42	42	-	-	20	22	38	79	-	-	20	22	25	25	15	20	16
PH 95-A	100	95	offen	42	46	46	46	-	-	22	28	-	-	95 (Spezialschliff)	-	-	-	-	-	-	-	-
PH 100-AG	74	100	geschlossen	42	46	42	46	-	-	-	28	-	-	100	100	-	-	-	-	-	-	-
PH 105	124	105	offen	105	105	105	105	-	-	-	-	-	-	105	-	-	-	-	-	-	-	-
PH 120-A	100	120	geschlossen	42	46	42	46	-	-	24	24	-	-	-	-	-	-	-	-	-	-	-
PH 132	95	132	geschlossen	42	46	42	46	-	-	-	-	-	-	130	130	-	-	-	-	-	-	-
KS33	-	33	geschlossen	20	23	33	33	33	-	-	-	-	-	-	-	-	-	-	-	-	-	-
KS52	-	52	geschlossen	23	25	52	52	52	-	-	-	-	-	-	-	-	-	-	-	-	-	-