

## Battery-operated Hydraulic Cutting Tool

# CUTMAX-C3

### Technical Data

|                              |                   |
|------------------------------|-------------------|
| <b>Cutting Force</b>         | 60 kN             |
| <b>Opening Width</b>         | 30 mm             |
| <b>Battery Voltage</b>       | 18 V              |
| <b>Weight*</b>               | 3.8 kg            |
| <b>Dimensions* L x W x H</b> | 393 x 82 x 283 mm |
| <b>Head</b>                  | 180° rotatable    |

\* without battery

MasterBase technology offers the following battery options, select your tool here:

| Item No. | Item               | Suitable for batteries from |
|----------|--------------------|-----------------------------|
| 72633000 | CutMax-C3 Ma       | Makita 18 V                 |
| 72643000 | CutMax-C3-Set Ma** | Makita 18 V                 |
| 72673100 | CutMax-C3 Bo       | Bosch 18 V                  |
| 72683100 | CutMax-C3-Set Bo** | Bosch 18 V                  |
| 72673000 | CutMax-C3 Hi       | Hilti 22 V (B22)            |
| 72069900 | CutMax-C3 HiN      | Hilti 22 V (Nuron)*         |
| 72067500 | CutMax-C3 Mi       | Milwaukee 18 V              |

\* Time required to connect the battery to the tool: 2 s



You can cover a wide range of applications with this battery-operated hydraulic cutting tool - it cuts wire rope, cables, contact wires as well as solid conductors; with an optional fine grinding you can even cut fine / very fine stranded conductors. The open cutting geometry makes working with the CutMax-C3 particularly easy and inspires users from the industry and traffic engineering.

### Top Features Comfort Serie "CutMax-C3"

- » Equipped with MasterBase technology for flexible selection of the Makita, Bosch or Hilti battery
- » Automatic return simplifies the work process
- » Fatigue-free working through balanced ergonomics
- » Lockable start button ensures work safety
- » LED working field illumination
- » Does the Comfort Series tool not have the right battery holder? **Retrofit** will make it fit.

### Cutting Ranges

| Application            | Cutting Ø                                      |  |
|------------------------|--|--|
| <b>Cu Strand</b>       | Ø 28 mm  |  |
| <b>Al Strand</b>       | Ø 28 mm  |  |
| <b>Cu Energy Cable</b> | Ø 28 mm  |  |
| <b>Al Energy Cable</b> | Ø 28 mm  |  |
| <b>Telephone Cable</b> | Ø 20 mm  |  |
| <b>Wire Rope</b>       | 6x7: Ø 18 mm<br>6x12: Ø 24 mm<br>6x19: Ø 24 mm |  |
| <b>Guy Wire</b>        | 1x17: Ø 20 mm<br>1x19: Ø 20 mm                 |  |

A sample processing is recommended.

#### \*\*Scope of Delivery Sets:

**72643000:** CutMax-C3 Ma, Makita battery 18 V/5 Ah BL1850B (item no. 79300115), Makita charger DC18RC (item no. 79300120), carrying strap, case (item no. 79500112)

**72683100:** CutMax-C3 Bo, Bosch battery PRO GBA 18V 5.0Ah (item no. 79300122), Bosch charger PRO GAL 1880CV (item no. 79300123), carrying strap, case (item no. 79500112)