Vacuum Pump DLP2500 series



Electric Screwdrivers can be used with Vacuum Pump and Vacuum Pickup. The sleeve of Vacuum Pickup sucks the screw and holds it on the bit, enabling the operator to pick it up with the tool itself, thus improving operational efficiency and operator's productivity.

Model		DLP2530	DLP2570	
Features		Standard	With CE mark	
Power Source		100 V AC, 50/60 Hz	230 V AC, 50/60 Hz	
Power Consumption	(W)	30(50 Hz), 26(60 Hz)		
Achievable Vacuum	(kPa)	-21.3		
Flow Rate (at Outlet)	(L/min)	24(50 Hz), 26(60 Hz)		
Screw Size	(mm)	4 or less		
Mass	(g [lbs])	3800 [8.38]		

Torque Adjustment Ring Cover

Accessories



Fits over torque adjustment ring cover to minimize tampering or accidental turning once the torque is set.

Model	Part No.	Applicable Screwdriver	Material
DLW5200	TD00331	DLV7100, DLV7200, DLV8100 and DLV8200 series	Aluminum
DLW5201*	TD05639	05639 DLV7100, DLV7200, DLV8100 series and DLV30A (Transformerless type)	
DLW5202	75202 TD08486 DLV45S, DLV70S and DLV45A, DLV70A		Aluminum
DLW5203	W5203 TD09222 DLV30S and DLV30A (Low voltage type)		Plastic (ESD)
DLW5300	5300 TD00332 DLV7301, DLV7000, DLV8000 series (for 4 mm bit)		Aluminum
DLW5400	00 TD01883 DLV7301 series (for 6.35 mm bit)		Aluminum
DLW5500	500 TD00333 DLV7303 series (for 4 mm & 6.35 mm bit)		Aluminum
DLW5600	V5600 TD00334 DLV7500, DLV8500 series		Plastic
DLW5700	5700 TD02875 DLV5700, DLV5800, DLV7400A series		Aluminum
_	TV07315	DLV02SL-BKE, DLV12SL-BKE, DLV16SL-BKE series	
_	TV06787 DLV02SL-CKE, DLV12SL-CKE, DLV16SL-CKE series		Plastic

^{*} As this is a clear plastic cover, torque scale can be seen even after mounted on the screwdriver.

Tool Balancer





Easy to adjust tension by using handle.

Model	Nodel TW-06R		RW-3	RW-5	
Capacity (g [lbs])	200 to 600 [0.44 to 1.32]	500 to 1500 [1.1 to 3.31]	1000 to 3000 [2.2 to 6.61]	2500 to 5000 [5.51 to11.02]	
Stroke (m [inch])	1.5 [[59"]	2 [78.7"]		
Mass (g [lbs])	300	[0.66]	700 [1.54]	900 [1.98]	

Pistol Grip DLW2300/2300ESD

Accessories



Easy-to-attach grip suitable for horizontal operation.

Model	Applicable Screwdriver		
DLW2300 (Non-ESD)	DLV7104/DLV8104/DLV8204/DLV7100/DLV7200/ DLV8100/DLV8200/DLV7500-MKE/DLV8500-MKE/ DLV30A/DLV45A/DLV70A(Transformerless type) DLV30A/DLV45A/DLV70A(Low voltage, Non-ESD type)		
DLW2300ESD	DLV7500-BKE/DLV8500-BKE DLV45C/DLV30S/DLV45S/DLV70S DLV30A/DLV45A/DLV70A (Low voltage, ESD type)		

Shaker Box Made of Anti-electrostatic Resin



The screws will fall into the heads-up position for easier vacuum or magnetic pickup. The anti-electrostatic resin greatly reduces static build-up and dust attached to the shaker box.

Model		DLW3402	DLW3602	DLW3802
Part No.		TD04110	TD04111	TD04112
Hole Pitch	(mm [inch])	6 [0.24"]		8 [0.31"]
Hole Depth	(mm [inch])	13.5 [0.53"]		12.5 [0.49"]
No. of Holes		273	273	160
Screw Size	(mm)	1.7 to 2	2 to 2.6	3 to 4
External Dimensions		W142 x H25 x D94 (W5.60" x H0.98" x D3.70")		